PRODUCT INFORMATION



A Product of Valvoline Cummins Ltd.

Valvoline All Fleet Turbo 15W-40

PRODUCT DESCRIPTION

Valvoline All Fleet Turbo 15W-40, is an advanced, hitech heavy duty diesel engine oil, formulated with highly stable premium base stocks and specially developed additives, synthetic boosters and SDT™ (Special Dispersant Technology). Synthetic technology will resist oil thickening for a much longer time. Even under extreme operating conditions, it resists molecular tear or breakdown.

The well balanced formulation incorporating of synthetic technology for Valvoline All Fleet Turbo 15W-40 ensures molecular uniformity resulting in enhanced chemical stability of oil and durability of the all engine components.

Unique dispersant technology, SDT™, with premium base oil ensures thermal and oxidation stability at severe operating conditions. It provides all round protection to the engine and to the delicate Turbo Charger resulting in enhanced engine life.

APPLICATIONS

It is recommended for TATA Motors, Ashok Leyland & Other Commercial vehicles. Recommended for use in new generation HCV's and LCV's plying at long haul. Also recommended for Mahindra & Mahindra and all other makes of MUV's and high horse power tractors. It is also recommended for gensets, construction & mining equipments.

PERFORMANCE STANDARS

API CH-4

ADVANTAGES

- Very high thermo-oxidative stability
- **Excellent TBN retention**
- SDT™ ensures excellent soot control / less sludge formation
- Lesser top-ups
- Enhanced rust & wear protection

TYPICAL CHARACTERSTICS

Kinematic Viscosity, cSt @ 40°C 113.20 Kinematic Viscosity, cSt @ 100°C 14.67 Pour Point, °C max. -30 TBN, mg KOH/g (ASTM 2896) 10 Flash Point, COC, °C, Min. 200

Available Packs: 1, 5, 7.5, 10, 15, 20, 50 & 210 Ltrs.

01/2010





'A' Square, 4th & 5th Floor, 278, Udyog Vihar, Phase II, Gurgaon, Haryana – 122 016 Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299



