OSYRIS 2626 TP





Long term rust preventive oil

PRODUCT PROFILE



Osyris 2626 TP is a unique blend of refined hydrocarbon, synthetic dialkyl ester and film forming dewatering additives. These additives wet the metal surface and displace the moisture while hydrocarbon present evaporates to form a thin soft greasy film to compact the effect of corrosion. Exhibit good salt spray and humidity resistance character

APPLICATIONS

For the protection of precious engineering, auto components as well as steel strip & tubes from corrosion.

ADVANTAGES

- Reduces rejection and cost of poor quality due to its excellent rust prevention character
- Balanced hydrocarbon base helps in reducing evaporation loss thus avoid **thickening of fluid and excessive consumption.**
- Built-in adjuvant helps in quicker displacement of water and settling of sludge thus **improves aesthetics and productivity**.
- Lower surface tension nature helps in **increased spread ability, shorten draining time and wastage.** Brings down consumption of oil/component
- Versatile in humid atmosphere due to its non-emulsifying nature.

Typical Characteristics	Reference Method	OSYRIS 2626 TP
Density at 29.5°C	ASTM D 1298	0.812
Flash point PMCC, °C	ASTM D 93	40
Water Displacement	IS 1154	Passes
Film thickness (microns)	IS 2079	4- 5
Finger print test	Internal	Passes
Protection – Indoor	Internal	6- 9 month
Outdoor		2 months

TOTAL LUBRICANTS INDIA LTD.

Head Office: 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel.: 022 66407700 Fax: 022 66407720 Regional Offices: Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6 Date 01/09

1/2

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be down loaded from

Head Office: 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel.: 022 66407700 Fax: 022 66407720 Regional Offices: Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be down

TOTAL LUBRICANTS INDIA LTD.

Date 01/09 2/2

loaded from www.quick-fds.com.