

# PRODUCT INFORMATION



A Product of Valvoline Cummins Ltd.

## Valvoline Waylube 32 / 68 / 220

### PRODUCT DESCRIPTION

Valvoline Waylube 32 / 68 / 220 are stable, high quality oils specially compounded to provide efficient lubrication of machine slide-ways. They are adhesive, tacky and resist stick-slip, thereby assuring smooth, efficient operation.

These products have excellent extreme pressure and film-strength properties and meet the exact demand of slide way lubrication in grinders, planners, milling machines and other equipment having slow moving parts.

### PERFORMANCE STANDARDS

Waylube 32: Cincinnati Milacron P 47  
Waylube 68: Cincinnati Milacron P 47  
Waylube 220: Cincinnati Milacron P 50

### TYPICAL CHARACTERISTICS

### VALVOLINE WAYLUBE

ISO VG	32	68	220
Kinematic Viscosity, cSt, @ 40 °C	32	68	220
Viscosity Index	95	95	95
Flash Point, COC, °C, min.	208	210	222

Available Pack: 20, 210 Ltrs.

9/2008



Valvoline Cummins Ltd.  
A Joint Venture Company of  
Valvoline International Inc., USA  
& Cummins Diesel Sales and Service (India) Ltd.  
52, Okhla Industrial Estate, Phase III, New Delhi – 110 020  
Phone: (011) 41613444 – 48, Fax: (011) 41613453  
Visit us at: [www.valvolinecummins.com](http://www.valvolinecummins.com)

